

# Model RS50, RS100, RS150, RS250



<b>Manufacturer</b>	Steam Sauna, Inc.			
<b>Service</b>	Residential Steam Generator			
<b>Operating Pressure</b>	Atmospheric			
<b>Model</b>	RS50	RS100	RS150	RS250
<b>Output</b>	3.0 KW	4.5 KW	6.5 KW	9.0 KW
<b>Amps</b>	13	19	27	38
<b>Electrical</b>	240 Volts, Single Phase			
<b>Dimensions</b>	17"L x 7"W x 10"H (models R) / 24"L x 7"W x 10"H (models AF & MF)			
	R: Regular (no drain), AF: Automatic Flush, MF: Manual Flush			
<b>Water Feed</b>	1/4" copper tube			
<b>Electronic Control Module</b>	Contains a P.C. board that controls the heating unit, water level and flush drain using a specific application, factory preset microprocessor with 90 min auto shut off safety feature			
<b>Elements</b>	Low density industrial incoloy heating elements			
<b>Operational Supply Valve</b>	one- 1/4" c/w compression connector for 1/4" tube			
<b>Auto Flush Valve</b>	one - 1/2" c/w compression connector for 1/2" copper pipe			
<b>Steam Outlet Pipe</b>	one - 1/2" c/w compression connector for 1/2" copper pipe			
	one - 3/4" c/w outlet for safety relief valve			
<b>Safety Relief Valve</b>	10 PSI or less			